

Auxiliary Switches



Honeywell Auxiliary Switches work with Honeywell models of 3-pole contactors.

| Honeywell Auxiliary Switches | | | | | | |
|------------------------------|----------|---------------------------------------|-------------------------------|--------------------------------|--|----------------------------|
| Product Number | Circuits | Configuration | Dimensions (in.) H x W x D | Contact Ratings (Resistive) | Maximum (inrush) Current at 120/240/480/600 V | Use With |
| DP3AUX-1NO | 1 | Normally Open snap-on | 2 26/32 x 2 17/32 x 7/16 | 10 A | 60/30/15/12 Amps | DP3030 – DP3090 Contactors |
| DP3AUX-1NC | 1 | Normally Closed snap-on | | | | |
| DP3AUX-1NO-1NC | 2 | Normally Closed/Normally Open snap-on | | | | |
| DP3AUX-2NO | | Normally Open snap-on | | | | |
| DP3AUX-2NC | | Normally Closed snap-on | | | | |

Fan Centers



Fan centers (combines a relay and a transformer), R8285 and R8239 NEMA-rated units offer low-voltage control of line-voltage fan motors and auxiliary circuits in heating, cooling or air-conditioning systems.

| Fan Centers | | | | | | | | | |
|-------------------------|---------------------------------------|-------------------------|-------------------|------------|----------------------------|------------------|-----------------------|-----------|------------------|
| Electrical Ratings (VA) | Electrical Ratings (Input Voltage) | Switching | Product Number | NEMA Rated | Dimensions (in.) H x W X D | Main Connections | Secondary Connections | Frequency | Special Features |
| 40 VA | 120 Vac | DPDT | R8239B1043 | Yes | 4 1/2 x 4 3/16 x 3 3/32 | L | L | A | Super Tradeline* |
| | | DPST | R8239D1007 | | | | | | Tradeline |
| | | DPST (1 Power, 1 Pilot) | R8239D1015 | | | | | | Tradeline |
| | | SPDT | R8239A1052 | | | | | | Tradeline |
| 50 VA | 120/208/240 Vac | DPDT | R8239B1076 | No | 4 3/16 x 4 1/2 x 2 13/16 | L | L | A | Super Tradeline |
| 40 VA | 120 Vac | SPDT | R8285A1048 | | | | | | Tradeline |
| | 120/208/240 Vac | DPDT | R8285B1053 | | | | | | Tradeline |
| 50 VA | 120 Vac | DPDT | R8285D5001 | | | | | | Tradeline |

| | | | |
|--------------|---------------------------------|-------|--------------------------|
| Frequency: | A — 60 Hz/50 Hz; B — 60 Hz | SPST: | Single Pole Single Throw |
| Approvals: | UL, CSA | DPST: | Double Pole Single Throw |
| Temp Rating: | -20° F to +105° F | DPDT: | Double Pole Double Throw |
| Connectors: | L — Leadwires | SPDT: | Single Pole Double Throw |
| Mounting: | Standard 4 x 4 in. junction box | | |

* Super Tradeline models include extra hardware.